## FORM U-1A MANUFACTURERS' DATA REPORT FOR UNFIRED PRESSURE VESSELS Alternate Form for Single Chamber Completely Shop-Fabricated Vessels Only

. Manufactured by AMF BEAIRD, INC., SHREVEPORT, LOUISIANA (Name and address of Manufacturer)	
	_
Manufactured for NORTH SHORE GAS COMPANY, CHICAGO, ILLINOIS SHIP C/O NORTH SHORE INSTALLATION	
(Name and address of Purchaser) MUNDELEIN, ILLINOIS	
Horiz. Vessel No. (182750-01-12) (State & State No.) Natl. Bd. No. 85831 Yt. Built 1971  (Mire. Serial) Nom. 15/16 Corr. 10 000 // 5-1/4	mun
SHELL: Matl. SA-515-70 T.S. 70,000% Thk. In. Allow 0 In. Diam.10 Ft. 10 In. Length 80 Ft. In. (Rind and Spec. No.) (Fig. or F.B. & Spec. Min. T.S.)	ר
S. SEAMS: Long Dbl. Butt H.T. No R.T.Complete Sectioned No Efficiency 100 % If rivered complete Sectioned No Efficiency 100 % If rivered described to the section of the se	
Girth Dbl. Butt H.T. No R.T.Complete Sectioned No No. of Courses 11 remarks.	<u>"</u> ]
6. HEADS: (a) Material SA-455-B T.S. 73.000# (b) Material Conical Homisphorical Fist Side to Pressure  (Top, bottom, ends) Thickness Radius Ratio Apex Angle Radius Diameter (Convex or Concav	
(Top, bottom, ends) Thickness Redius Redius Ratio Apex Angle Radius Diameter (Convex or Concave 65.0235" Concave	"
(b)	_
If removable, bolts used (Material, Spec. No., Y.S., Size, Number) (Describe or Attach Sketch)	<del></del> -
Hudmararic )	
7. Constructed for max.  Min. temp. (when allowable working press. 2 250 psi at max. temp. 150 °F. less than -20°) F. Combination Press 375 p	si.
3. SAFETY OR RELIEF VALVE OUTLETS: Number 2 Size 4" Location Top of tank in she	11
D. NOZZLES:	-
Oulet, Drain) Number Diam, or Size Type Material Thickness Material Attached	
(1) 3/4" 6000# Cplg. SA-105-II (1) 3/4" Sch. 80 Seamless Pipe (Thermowell) SA-106-B Welded	
(1) 2" (1) 3" 300# Drilled & Tapped Pad Type Flgs.       SA-515-70 Welded         (2) 4" 300# Drilled Pad Type Flgs.       SA-515-70 Welded	
(1) 2-1/2" Special (Slip on Type) Flg. SA-106-B SA-515-70 3/8" SA-515-70 Welded	
(2) 3/4" (1) 2" (1) 3" Drilled & Tapped Holes in Manway Cover	
). INSPECTION Manholes, No. 1 Size 18" Location Pad 7/8" SA-515-70 Neck 3/8"	
OPENINGS: Handholes, No. Size Location SA-515-70 Flg. 300# S.O. SA-181-	1
Threaded, No. Size Location Top of tank in shell	
a. (2) Saddles Shipped loose	
1. SUPPORTS: Skirt Lugs Legs Other (2) Sadutes Attached Stillphed 1005e	
2. REMARKS: 130" I.D. x 91' 9-3/16" O.A. Length 60,248 W.G. Propane Storage Tank, per Beaird	
2. REMARKS: 130" I.D. x 91' 9-3/16" O.A. Length 60,248 W.G. Propane Storage Tank, per Beaird	
P. REMARKS: 130" I.D. x 91' 9-3/16" O.A. Length 60,248 W.G. Propane Storage Tank, per Beaird Dwg. Order 182750-01	
2. REMARKS: 130" I.D. x 91' 9-3/16" O.A. Length 60,248 W.G. Propane Storage Tank, per Beaird  Dwg. Order 182750-01  * Head seams Spot X-rayed Joint Eff. 85%	
2. REMARKS: 130" I.D. x 91' 9-3/16" O.A. Length 60,248 W.G. Propane Storage Tank, per Beaird  Dwg. Order 182750-01	
2. REMARKS: 130" I.D. x 91' 9-3/16" O.A. Length 60,248 W.G. Propane Storage Tank, per Beaird  Dwg. Order 182750-01  * Head seams Spot X-rayed Joint Eff. 85%  (Brief description of purpose of the vessel as Air Tank, Water Tank, L.P.G., Etc.—State Contents.  1 B postupoid heat-treated.  List other internal or external pressures with coincident temperature when applicable.  We certify that the statements made in this report are correct and that all details of design, material, construction, and workmanship of this report.	
** Head seams Spot X-rayed Joint Eff. 85%  ** Head seams Spot X-rayed Joint Eff. 85%  ** In the seams Spot X-rayed Joint Eff. 85%  ** Tank, Water Tank, L.P.G., Etc.—State Contents.  ** If postweld heat-treated.  ** It postweld heat-treated.  ** Lies other internal or external pressures with coincident temperature when applicable.  ** We certify that the statements made in this report are correct and that all details of design, material, construction and workmanship of this seafers to the ASME Code for Unified Pressure Vessels.  ** 8-19 . 1971 Signed AMF BEAIRD, INC.  ** By O. F. Samehar A. Samehar A. Samehar A. Signed AMF BEAIRD, INC.  ** By O. F. Samehar A. Same	
* Head seams Spot X-rayed Joint Eff. 85%  ** Head seams Spot X-rayed Joint Eff. 85%  ** Big description of purpose of the vessel as Air Tank, Water Tank, L.P.G., Etc.—State Contents.  ** By postweld heat-treated.  ** List other internal pressures with coincident temperature when applicable.  ** We certify that the statements made in this report are correct and that all details of design, material, construction and workmanship of this vessel to the ASME Code for United Pressure Vessels. 1968 Edition Div. 1	
* Head seams Spot X-rayed Joint Eff. 85%  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Brief description of purpose of the vessel as Air Tank, Water Tank, L.P.G., Etc.—State Contents.  ** If postweld heat-treated.  ** Lies other internal or external pressures with coincident temperature when applicable.  ** We certify that the statements made in this report are correct and that all details of design, material, construction and workmanship of this vessel to the ASME Code for United Pressure Vessels.  ** 1968 Edition Div. 1  ** Bealing Code for United Pressure Vessels.  ** Signed AMF BEAIRD, INC.  ** Unanufacturer.  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** (Benufacturer)  ** Head seams Spot X-rayed Joint Eff. 85%  ** Head seams Spot	
* Head seams Spot X-rayed Joint Eff. 85%  ** Head seams Spot X-rayed Joint Eff. 85%  ** By postword heat-treated.  ** List other internal or external pressures with coincident temperature when applicable.  ** We certify that the statements made in this report are correct and that all details of design, material, construction and workmanship of this received to the ABME Code for Unfired Pressure Vessels.  ** 1968 Edition Div. 1  ** Benulacturer;  ** Certificate of Authorization Expires December 31, 1974	
2. REMARKS: 130" I.D. x 91' 9-3/16" O.A. Length 60,248 W.G. Propane Storage Tank, per Beaird Dwg. Order 182750-01  * Head seams Spot X-rayed Joint Eff. 85%  (Brief description of purpose of the vessel as Air Tank, Water Tank, L.P.G., EtcState Contests.  * List other internal or external pressures with coincident temperature when applicable.  * Ve certify that the statements made in this report are correct and that all details of design, material, construction and workmanship of this vessel to the ASME Code for Unifered Pressure Vessels. 1968 Edition Div. 1  ** AMF BEAIRD, INC.  ** CERTIFICATE OF SHOP INSPECTION  ** VESSEL MADE BY AMF BEAIRD, INC.  ** SHREVEPORT, LOUISIANA  I, the undersigned, helding a valid commission issued by the National Board of Boiler and Pressure Vessel Impectors and/or	
(Brief description of purpose of the vessel as Air Tank, Water Tank, L.P.G., Etc.—State Contents.  If postweld heat-treated.  List other internal pressures with coincident temperature when applicable.  We certify that the statements made in this report are correct and that all details of design, material, construction and workmanship of this vessers to the ASME Code for Unifered Pressure Vessels. 1968 Edition Div. 1  AMF BEAIRD, INC.  By  CERTIFICATE OF SHOP INSPECTION  VESSEL MADE BY  AMF BEAIRD, INC.  at SHREVEPORT, LOUISIANA	
2. REMARKS: 130" I.D. x 91' 9-3/16" O.A. Length 60,248 W.G. Propane Storage Tank, per Beaird Dwg. Order 182750-01  * Head seams Spot X-rayed Joint Eff. 85%  (Brief description of purpose of the vessel as Air Tank, Vator Tank, L.P.G., Etc.—State Contents.  * B postweld heat-treated.  * List other internal or external pressures with coincident temperature when applicable.  * We certify that the statements made in this report are correct and that all details of design, material, construction and workmanship of this vesser to the ABME Cede for Unifred Pressure Vessels. 1968 Edition Div. 1  ate 8-19 . 1971 Signed AMF BEAIRD, INC.  * CERTIFICATE OF SHOP INSPECTION  ** VESSEL MADE BY AMF BEAIRD, INC.  I, the undersigned, helding a valid commission issued by the National Board of Boiler and Pressure Vessel Inspectors and/or the State or Province N. B. and employed by EMPLOYERS COMMERCIAL UNION INSURANCE CO. of	
2. REMARKS: 130" I.D. x 91' 9-3/16" O.A. Length 60,248 W.G. Propane Storage Tank, per Beaird Dwg. Order 182750-01  * Head seams Spot X-rayed Joint Eff. 85%.  (Brief description of purpose of the vessel as Air Tank, Water Tank, L.P.G., Etc.—State Contents.  If postword heat-treated.  List other internal or external pressures with coincident temperature when applicable.  We certify that the statements made in this report are correct and that all details of design, material, construction and workmanship of this vessel to the ASME Cede for Unitered Pressure Vessels. 1968 Edition Div. 1  ARE 8-19 . 1971 Signed AMF BEAIRD, INC.  (Manufacturer)  Certificate of Authorization Expires December 31, 1974  CERTIFICATE OF SHOP INSPECTION  VESSEL MADE BY AMF BEAIRD, INC. at SHREVEPORT, LOUISIANA  I, the undersigned, holding a valid commission issued by the National Board of Boiler and Pressure Vessel Impoctors and/or the State or Province N. B. and employed by EMPLOYERS COMMERCIAL UNION INSURANCE CO. of have inspected the pressure vessel described in this manufacturer's	
2. REMARKS: 130" I.D. x 91' 9-3/16" O.A. Length 60,248 W.G. Propane Storage Tank, per Beaird    Dwg. Order 182750-01	
** Head seams Spot X-rayed Joint Eff. 85%  ** Whead seams Spot X-rayed Joint Eff. 85%  ** (White description of purpose of the vessel as Air Tenk, Water Tank, L.P.G., Etc.—State Centents.  ** List other internal or extremal pressures with coincident temperature when applicable.  ** We certify that the statements made in this report are correct and that all details of design, material, construction and workmanship of this vessel to the ABME Code for Unified Pressure Vessels.  ** 1968 Edition Div. 1  ** December 31, 1974  ** Certificate of Authorization Expires December 31, 1974  ** The undersigned, heiding a valid commission issued by the National Board of Boiler and Pressure Vessel impectors and/or the State or Province N. B. and employed by EMPLOYERS COMMERCIAL UNION INSURANCE CO. of have inspected the pressure vessel described in this manufacturer's data report on 8-19 1971, and state that to the best of my knowledge and belief, the manufacturer base constructed this pressure vessel in accordance with the applicable sections of the ABME Boiler and Pressure Vessel Code.  ** By signing this certificate neither the Inspector nor his employer makes any warranty, expressed or implied, concerning the pressure vessel described in this manufacturer's data report. Furthermore, neither the Inspector nor his employer shall be liable in any	
2. REMARKS: 130" I.D. x 91' 9-3/16" O.A. Length 60,248 W.G. Propane Storage Tank, per Beaird    Dwg. Order 182750-01	
** Head seams Spot X-rayed Joint Eff. 85%.  (Brief description of purpose of the vessel as Air Tenk, Water Tank, L.P.G., Etc.—State Contents.  ** Head seams Spot X-rayed Joint Eff. 85%.  (Brief description of purpose of the vessel as Air Tenk, Water Tank, L.P.G., Etc.—State Contents.  ** Head seams Spot X-rayed Joint Eff. 85%.  (Brief description of purpose of the vessel as Air Tenk, Water Tank, L.P.G., Etc.—State Contents.  ** Head seams Spot X-rayed Joint Eff. 85%.  (Brief description of purpose of the vessel as Air Tenk, Water Tank, L.P.G., Etc.—State Contents.  ** Head seams Spot X-rayed Joint Eff. 85%.  We certify that the statements made in this report are correct and that all details of design, material, construction and workmanship of this vessel as Air Tenk, Water Tank, L.P.G., Etc.—State Contents.  ** Head seams Spot X-rayed Joint Eff. 85%.  We certify that the statements made in this report are correct and that all details of design, material, construction and workmanship of this vessel as Edition Div. 1  ** AMF BEAIRD, INC.  ** By HREVEPORT, LOUISIANA  I, the undersigned, heiding a velid commission issued by the National Board of Boiler and Pressure Vessel Impectors and/or the State or Province N, B. and employed by EMPLOYERS COMMERCIAL UNION INSURANCE CO. of have inspected the pressure vessel described in this manufacturer's data report on 1971, and state that to the best of my knowledge and belief, the manufacturer has constructed this pressure vessel in accordance with the applicable sections of the ASME Boiler and Pressure Vessel Code.  **By signing this certificate neither the Inspector nor his employer makes any warranty, expressed or implied, concerning the pressure vessel described in this manufacturer's data report. Furthermore, neither the Inspector nor his employer shall be liable in any manner for any personal injury or property damage or a lose of any kind arising from or connected with this inspection.  **AMF BEAIRD, INC.**  **Brain Tank, Tank, L.P.G., Etc.—State Contents.  **AMF BEAIR	